



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 21

LOCTITE 3D 3860 HDT180 High Heat Black

SDS No. : 629817
V003.1

Revision: 06.09.2022

printing date: 22.03.2023

Replaces version from: 14.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 3D 3860 HDT180 High Heat Black

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Dicyclopentylidimethylene diacrylate

2,2'-Ethylenedioxydiethyl dimethacrylate
Hydroxypropyl methacrylate
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Signal word: Warning

Hazard statement: H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: P273 Avoid release to the environment.
Prevention P280 Wear protective gloves.

Precautionary statement: P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
Response

2.3. Other hazards

None if used properly.
Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Care should be taken during the cure of these products by UV radiation to avoid exposure of the skin and especially of the eyes to direct or reflected UV radiation as long term effects could be harmful.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|--|----------------------|--|---|-------------------------|
| Dicyclopentylidimethylene diacrylate 42594-17-2 255-901-3 01-2120051112-76 | 50- 100 % | Skin Sens. 1B, H317 Aquatic Chronic 2, H411 | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 203-652-6 01-2119969287-21 | 5- < 10 % | Skin Sens. 1B, H317 | dermal:ATE = > 5.000 mg/kg inhalation:ATE = 28,17 mg/l;dust/mist | |
| Hydroxypropyl methacrylate 27813-02-1 248-666-3 01-2119490226-37 | 1- < 5 % | Skin Sens. 1, H317 Eye Irrit. 2, H319 | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 423-340-5 01-2119489401-38 01-2119936813-33 | 0,1- < 1 % | Skin Sens. 1A, H317 Aquatic Chronic 4, H413 | | |
| Acrylic acid 79-10-7 201-177-9 01-2119452449-31 | 0,1- < 1 % | Acute Tox. 4, Dermal, H312 Skin Corr. 1A, H314 Flam. Liq. 3, H226 Acute Tox. 4, Oral, H302 Acute Tox. 4, Inhalation, H332 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 STOT SE 3, H335 | STOT SE 3; H335; C >= 1 % ===== M acute = 1 ===== dermal:ATE = 1.100 mg/kg inhalation:ATE = 11 mg/l;vapour | EU OEL |

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Ventilation will remove any ozone that may be produced by the ultra violet lamp

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-----------------------------------|--|-----------------|
| Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)] | 10 | 29 | Time Weighted Average (TWA): | Indicative | ECLTV |
| Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)] | 20 | 59 | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Acrylic acid 79-10-7 [ACRYLIC ACID] | 10 | 29 | Time Weighted Average (TWA): | | EH40 WEL |
| Acrylic acid 79-10-7 [Acrylic acid] | 20 | 59 | Short Term Exposure Limit (STEL): | 1 minute | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-----------------------------------|--|-----------------|
| Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)] | 10 | 29 | Time Weighted Average (TWA): | Indicative | ECLTV |
| Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)] | 20 | 59 | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Acrylic acid 79-10-7 [ACRYLIC ACID] | 20 | 59 | Short Term Exposure Limit (STEL): | 1 minute Indicative OELV | IR_OEL |
| Acrylic acid 79-10-7 [ACRYLIC ACID] | 10 | 29 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|--|------------------------------|-----------------|--------------|-----|--------------|--------|----------------------------------|
| | | | mg/l | ppm | mg/kg | others | |
| (Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2 | aqua (freshwater) | | 0,0016 mg/l | | | | |
| (Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2 | aqua (marine water) | | 0,00016 mg/l | | | | |
| (Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2 | sediment (freshwater) | | | | 0,6576 mg/kg | | |
| (Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2 | sediment (marine water) | | | | 0,0658 mg/kg | | |
| (Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2 | Soil | | | | 0,1306 mg/kg | | |
| (Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| (Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2 | aqua (intermittent releases) | | 0,016 mg/l | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | aqua (freshwater) | | 0,164 mg/l | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | aqua (marine water) | | 0,0164 mg/l | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | aqua (intermittent releases) | | 0,164 mg/l | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sediment (freshwater) | | | | 1,85 mg/kg | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sediment (marine water) | | | | 0,185 mg/kg | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Soil | | | | 0,274 mg/kg | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Air | | | | | | no hazard identified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Predator | | | | | | no potential for bioaccumulation |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | aqua (freshwater) | | 0,904 mg/l | | | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | aqua (marine water) | | 0,904 mg/l | | | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | aqua (intermittent releases) | | 0,972 mg/l | | | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | sediment (freshwater) | | | | 6,28 mg/kg | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | sediment (marine water) | | | | 6,28 mg/kg | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | Soil | | | | 0,727 mg/kg | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | Marine water - intermittent | | 0,972 mg/l | | | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | Air | | | | | | no hazard identified |
| Methacrylic acid, monoester with propane-1,2-diol | Predator | | | | | | no potential for bioaccumulation |

| | | | | | | | |
|---|------------------------------|--|-------------|--|---------------|--|----------------------|
| 27813-02-1 | | | | | | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | aqua (freshwater) | | 0,001 mg/l | | | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | aqua (intermittent releases) | | 0,001 mg/l | | | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | aqua (marine water) | | 0,001 mg/l | | | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | sewage treatment plant (STP) | | 1 mg/l | | | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | sediment (freshwater) | | | | 0,712 mg/kg | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | sediment (marine water) | | | | 0,712 mg/kg | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | Soil | | | | 20 mg/kg | | |
| Acrylic acid 79-10-7 | aqua (freshwater) | | 0,003 mg/l | | | | |
| Acrylic acid 79-10-7 | aqua (marine water) | | 0,0003 mg/l | | | | |
| Acrylic acid 79-10-7 | sewage treatment plant (STP) | | 0,9 mg/l | | | | |
| Acrylic acid 79-10-7 | sediment (freshwater) | | | | 0,0236 mg/kg | | |
| Acrylic acid 79-10-7 | sediment (marine water) | | | | 0,00236 mg/kg | | |
| Acrylic acid 79-10-7 | Soil | | | | 1 mg/kg | | |
| Acrylic acid 79-10-7 | oral | | | | 0,03 g/kg | | |
| Acrylic acid 79-10-7 | Air | | | | | | no hazard identified |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|--------------------|-------------------|---|---------------|------------------------|----------------------|
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Workers | inhalation | Long term exposure - systemic effects | | 48,5 mg/m ³ | no hazard identified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Workers | dermal | Long term exposure - systemic effects | | 13,9 mg/kg | no hazard identified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | General population | inhalation | Long term exposure - systemic effects | | 14,5 mg/m ³ | no hazard identified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | General population | dermal | Long term exposure - systemic effects | | 8,33 mg/kg | no hazard identified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | General population | oral | Long term exposure - systemic effects | | 8,33 mg/kg | no hazard identified |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | Workers | dermal | Long term exposure - systemic effects | | 4,2 mg/kg | no hazard identified |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | Workers | Inhalation | Long term exposure - systemic effects | | 14,7 mg/m ³ | no hazard identified |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | General population | dermal | Long term exposure - systemic effects | | 2,5 mg/kg | no hazard identified |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | General population | Inhalation | Long term exposure - systemic effects | | 8,8 mg/m ³ | no hazard identified |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | General population | oral | Long term exposure - systemic effects | | 2,5 mg/kg | no hazard identified |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | Workers | Inhalation | Long term exposure - systemic effects | | 21 mg/m ³ | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | Workers | dermal | Long term exposure - systemic effects | | 3 mg/kg | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | General population | inhalation | Long term exposure - systemic effects | | 5,2 mg/m ³ | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | General population | dermal | Long term exposure - systemic effects | | 1,5 mg/kg | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | General population | oral | Long term exposure - systemic effects | | 1,5 mg/kg | |
| Acrylic acid 79-10-7 | Workers | inhalation | Long term exposure - local effects | | 30 mg/m ³ | no hazard identified |
| Acrylic acid 79-10-7 | Workers | inhalation | Acute/short term exposure - local effects | | 30 mg/m ³ | no hazard identified |
| Acrylic acid 79-10-7 | Workers | dermal | Acute/short term exposure - local effects | | 1 mg/cm ² | no hazard identified |
| Acrylic acid 79-10-7 | General population | dermal | Acute/short term exposure - local effects | | 1 mg/cm ² | no hazard identified |
| Acrylic acid 79-10-7 | General population | inhalation | Acute/short term exposure - local effects | | 3,6 mg/m ³ | no hazard identified |
| Acrylic acid 79-10-7 | General population | inhalation | Long term exposure - local effects | | 3,6 mg/m ³ | no hazard identified |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

UV lamp should be designed, installed and operated in such a way as to eliminate exposure of the skin and eyes to stray radiation

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|--|--|
| Physical state | liquid |
| Delivery form | liquid |
| Colour | black |
| Odor | mild, Acrylic |
| Melting point | Not applicable, Product is a liquid |
| Initial boiling point | > 150 °C (> 302 °F) |
| Flammability | Not applicable |
| Explosive limits | Currently under determination |
| Flash point | > 93,3 °C (> 199.94 °F) |
| Auto-ignition temperature | Currently under determination |
| Decomposition temperature | Currently under determination |
| pH | Not applicable |
| Viscosity (kinematic) | Currently under determination |
| Viscosity, dynamic (Cone and plate; 25,0 °C (77 °F); Shear gradient: 200,00 s ⁻¹ ; Swell time: 180 s) | 200,00 - 600,00 mPa.s LCT STM 740; cone & plate viscosity |
| Solubility (qualitative) (Solvent: Water) | Partially soluble |
| Partition coefficient: n-octanol/water | Not applicable |

| | |
|--------------------------|---------------------------------|
| Vapour pressure | Mixture |
| Density | ;no method |
| () | 1,1 g/cm ³ no method |
| Relative vapour density: | Currently under determination |
| Particle characteristics | Not applicable |
| | Product is a liquid |

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.
Acids.
Reducing agents.
Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.
Protect from direct sunlight.
Avoid contact with acids and oxidizing agents.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.
Hydrocarbons
nitrogen oxides
Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 423 (Acute Oral toxicity) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | LD50 | 10.837 mg/kg | rat | not specified |
| Hydroxypropyl methacrylate 27813-02-1 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Phenyl bis(2,4,6- trimethylbenzoyl)- phosphine oxide 162881-26-7 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Acrylic acid 79-10-7 | LD50 | 1.500 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|-------------------------------|---------------|---------|--|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Acute toxicity estimate (ATE) | > 5.000 mg/kg | | Expert judgement |
| Hydroxypropyl methacrylate 27813-02-1 | LD50 | > 5.000 mg/kg | rabbit | not specified |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| Acrylic acid 79-10-7 | Acute toxicity estimate (ATE) | 1.100 mg/kg | | Expert judgement |
| Acrylic acid 79-10-7 | LD50 | > 2.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|--|-------------------------------|------------|-----------------|------------------|---------|---|
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Acute toxicity estimate (ATE) | 28,17 mg/l | dust/mist | | | Expert judgement |
| Acrylic acid 79-10-7 | LC0 | 5,1 mg/l | vapour | 4 h | rat | equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity) |
| Acrylic acid 79-10-7 | Acute toxicity estimate (ATE) | 11 mg/l | vapour | | | Expert judgement |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|------------------------|------------------|----------|--|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | not irritating | | In vitro | OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | not irritating | 24 h | rabbit | Draize Test |
| Hydroxypropyl methacrylate 27813-02-1 | not irritating | 24 h | rabbit | Draize Test |
| Acrylic acid 79-10-7 | Category 1 (corrosive) | 3 min | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|---|------------------|----------|---|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | not irritating | | In vitro | OECD Guideline 437 (BCOP) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Hydroxypropyl methacrylate 27813-02-1 | Category 2B (mildly irritating to eyes) | | rabbit | Draize Test |
| Acrylic acid 79-10-7 | Category 1 (irreversible effects on the eye) | | rabbit | BASF Test |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|--|----------------------------------|------------------------------------|------------|--|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | Sub-Category 1B (sensitising) | Freund's complete adjuvant test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Hydroxypropyl methacrylate 27813-02-1 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Hydroxypropyl methacrylate 27813-02-1 | sensitising | Guinea pig maximisation test | guinea pig | not specified |
| Acrylic acid 79-10-7 | not sensitising | Freund's complete adjuvant test | guinea pig | Klecak Method |
| Acrylic acid 79-10-7 | not sensitising | Split adjuvant test | guinea pig | Maguire Method |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---|----------|---|--|----------------------------|--|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | negative | in vitro mammalian cell micronucleus test | with and without | | OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test) |
| Hydroxypropyl methacrylate 27813-02-1 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Hydroxypropyl methacrylate 27813-02-1 | positive | in vitro mammalian chromosome aberration test | with and without | | Chromosome Aberration Test |
| Hydroxypropyl methacrylate 27813-02-1 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Acrylic acid 79-10-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Acrylic acid 79-10-7 | negative | mammalian cell gene mutation assay | with and without | | equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Acrylic acid 79-10-7 | negative | DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro | without | | equivalent or similar to OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells) |
| Hydroxypropyl methacrylate 27813-02-1 | negative | oral: gavage | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Hydroxypropyl methacrylate 27813-02-1 | negative | oral: gavage | | Drosophila melanogaster | not specified |
| Acrylic acid 79-10-7 | negative | oral: gavage | | rat | equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test) |
| Acrylic acid 79-10-7 | negative | oral: gavage | | mouse | not specified |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|---|------------------|-------------------------|---|---------|-------------|---|
| Hydroxypropyl methacrylate 27813-02-1 | not carcinogenic | inhalation | 2 y 6 h/d, 5 d/w | rat | male | equivalent or similar OECD Guideline 451 (Carcinogenicity Studies) |
| Acrylic acid 79-10-7 | not carcinogenic | oral: drinking water | 26 - 28 m continuously | rat | male/female | OECD Guideline 451 (Carcinogenicity Studies) |
| Acrylic acid 79-10-7 | not carcinogenic | dermal | 21 m 3 times/w | mouse | male/female | not specified |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|--|---|----------------------|----------------------|---------|--|
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg | | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Hydroxypropyl methacrylate 27813-02-1 | NOAEL P 300 mg/kg NOAEL F1 1.000 mg/kg | screening | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Hydroxypropyl methacrylate 27813-02-1 | NOAEL P 400 mg/kg NOAEL F1 400 mg/kg | two-generation study | oral: gavage | rat | OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |
| Acrylic acid 79-10-7 | NOAEL P 83 mg/kg NOAEL F1 250 mg/kg | one-generation study | oral: drinking water | rat | equivalent or similar to OECD Guideline 415 (One-Generation Reproduction Toxicity Study) |
| Acrylic acid 79-10-7 | NOAEL P 240 mg/kg NOAEL F1 53 mg/kg NOAEL F2 53 mg/kg | two-generation study | oral: drinking water | rat | OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|--|-------------------|----------------------|--|---------|--|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | NOAEL 1.000 mg/kg | oral: gavage | | rat | OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | NOAEL 1.000 mg/kg | oral: gavage | daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Hydroxypropyl methacrylate 27813-02-1 | NOAEL 300 mg/kg | oral: gavage | 49 d daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Hydroxypropyl methacrylate 27813-02-1 | NOAEL 0,352 mg/l | inhalation | 90 d 6 h/d, 5 d/w | rat | OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |
| Acrylic acid 79-10-7 | NOAEL 40 mg/kg | oral: drinking water | 12 m daily | rat | equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies) |
| Acrylic acid 79-10-7 | NOAEL 0,015 mg/l | inhalation: vapour | 90 d 6 h/d, 5 d/w | mouse | equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------------------------|---------------|---|--|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | LC50 | 1,65 mg/l | 96 h | Danio rerio | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | LC50 | 16,4 mg/l | 96 h | Danio rerio | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Hydroxypropyl methacrylate 27813-02-1 | LC50 | 493 mg/l | 48 h | Leuciscus idus melanotus | DIN 38412-15 |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | LC50 | Toxicity > Water solubility' | 96 h | Danio rerio | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Acrylic acid 79-10-7 | LC50 | 27 mg/l | 96 h | Salmo gairdneri (new name: Oncorhynchus mykiss) | EPA OTS 797.1400 (Fish Acute Toxicity Test) |
| Acrylic acid 79-10-7 | NOEC | >= 10,1 mg/l | 45 d | Oryzias latipes | OECD Guideline 210 (fish early lite stage toxicity test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-----------------------------|---------------|---------------|--|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | EC50 | 2,36 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Hydroxypropyl methacrylate 27813-02-1 | EC50 | > 143 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Acrylic acid 79-10-7 | EC50 | 95 mg/l | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-----------------------------|---------------|---------------|--|
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | NOEC | 32 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Hydroxypropyl methacrylate 27813-02-1 | NOEC | 45,2 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | NOEC | Toxicity > Water solubility | 21 day | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Acrylic acid 79-10-7 | NOEC | 19 mg/l | 21 d | Daphnia magna | EPA OTS 797.1330 (Daphnid Chronic Toxicity Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-----------------------------|---------------|---|---|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | EC50 | 1,6 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Dicyclopentylidimethylene diacrylate 42594-17-2 | EC10 | 0,64 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | EC50 | > 100 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | NOEC | 18,6 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Hydroxypropyl methacrylate 27813-02-1 | EC50 | > 97,2 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Hydroxypropyl methacrylate 27813-02-1 | NOEC | > 97,2 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | EC50 | Toxicity > Water solubility | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | NOEC | Toxicity > Water solubility | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Acrylic acid 79-10-7 | EC10 | 0,03 mg/l | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | EU Method C.3 (Algal Inhibition test) |
| Acrylic acid 79-10-7 | EC50 | 0,13 mg/l | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | EU Method C.3 (Algal Inhibition test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------|---------------|----------------------------|--|
| Hydroxypropyl methacrylate 27813-02-1 | EC10 | 1.140 mg/l | 16 h | | not specified |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | EC 50 | > 100 mg/l | 3 h | | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Acrylic acid 79-10-7 | EC20 | 900 mg/l | 30 min | activated sludge, domestic | ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge) |

12.2. Persistence and degradability

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|----------------------------|-----------|---------------|------------------|---|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | not readily biodegradable. | aerobic | 28 % | 28 day | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | readily biodegradable | aerobic | 85 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Hydroxypropyl methacrylate 27813-02-1 | readily biodegradable | aerobic | 94,2 % | 28 d | OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test) |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | not readily biodegradable. | aerobic | 1 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Acrylic acid 79-10-7 | inherently biodegradable | aerobic | 100 % | 28 d | OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test) |
| Acrylic acid 79-10-7 | readily biodegradable | aerobic | 81 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |

12.3. Bioaccumulative potential

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|---|-------------------------------|---------------|-------------|---------|---|
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | < 5 | | | | OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish) |
| Acrylic acid 79-10-7 | 3,16 | | | | QSAR (Quantitative Structure Activity Relationship) |

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|--------|-------------|--|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | 4,6 | | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | 2,3 | | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Hydroxypropyl methacrylate 27813-02-1 | 0,97 | 20 °C | not specified |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | 5,8 | | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Acrylic acid 79-10-7 | 0,46 | 25 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|---|---|
| Dicyclopentylidimethylene diacrylate 42594-17-2 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Hydroxypropyl methacrylate 27813-02-1 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Acrylic acid 79-10-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

| |
|--|
| SECTION 14: Transport information |
|--|

14.1. UN number or ID number

| | |
|------|------|
| ADR | 3082 |
| RID | 3082 |
| ADN | 3082 |
| IMDG | 3082 |
| IATA | 3082 |

14.2. UN proper shipping name

| | |
|------|---|
| ADR | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate) |
| RID | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate) |
| ADN | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate) |
| IMDG | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate) |
| IATA | Environmentally hazardous substance, liquid, n.o.s. ((Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate) |

14.3. Transport hazard class(es)

| | |
|------|---|
| ADR | 9 |
| RID | 9 |
| ADN | 9 |
| IMDG | 9 |
| IATA | 9 |

14.4. Packing group

| | |
|------|-----|
| ADR | III |
| RID | III |
| ADN | III |
| IMDG | III |
| IATA | III |

14.5. Environmental hazards

| | |
|------|------------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | Marine pollutant |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|-------------------------------|
| ADR | not applicable Tunnelcode: |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|---|----------------|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |
| VOC content (2010/75/EC) | < 3 % |

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

| | |
|-------------|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2: | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.